




HYDRALUX

SMARTER HOT WATER

**Flexible in design.
Quality you can
depend on.**



HYDRALUX
SMARTER HOT WATER





HYDRALUX

SMARTER HOT WATER



Hydralux is the smart thermal storage vessel built for Australian conditions. Standout quality at an understated price.

Hydralux leads the way in imported high performance thermal storage. Our vessels are manufactured from Duplex 2205 and hold Australian Electrical and Watermark Approvals. Hydralux is designed for ease of installation and endorsed by Wilson Hot Water – a benchmark for Australian customised hot water for over 90 years.



Storage



Single Coil

includes 3kW electric element




Twin Coil

includes 3kW electric element

A quality product from Wilson Hot Water

wilson
CUSTOMISED HOT WATER




Specifications

| Model # | Capacity Litres | Dimensions Dia x Height | Electric Boost 3kW | Storage | Single Coil Lower m ² 28mm Dia | Twin Coil Lower / Upper m ² 28mm Dia | Connections 6 x 50mm 2 x 25mm 2 x Thermowell Pockets |
|---------------------------|--------------------|----------------------------|-----------------------|---------|---|---|---|
| HSS100 (buffer tank) | 100 | 470 x 1035 | | ✓ | | | 4 x 40mm & 1 x 25mm 304 Stainless Steel 1 x Thermowell Pocket |
| HSS200 (buffer tank) | 200 | 470 x 1312 | | ✓ | | | 4 x 32mm & 1 x 25mm 304 Stainless Steel 1 x Thermowell Pocket |
| HSSE3151CW (heat pump) | 315 | 600 x 1985 | ✓ | | 4.5 | | ✓ |
| HSSE3152CF | 315 | 600 x 1985 | ✓ | | | 1.4 / 1.0 | ✓ |
| HSS400 | 400 | 700 x 1830 | | ✓ | | | ✓ |
| HSSE4001CF | 400 | 700 x 1830 | ✓ | | 1.8 | | ✓ |
| HSSE4002CF | 400 | 700 x 1830 | ✓ | | | 1.8 / 1.0 | ✓ |
| HSS600 | 600 | 700 x 2250 | | ✓ | | | ✓ |
| HSSE6001CF | 600 | 700 x 2250 | ✓ | | 2.5 | | ✓ |
| HSSE6002CF | 600 | 700 x 2250 | ✓ | | | 2.5 / 1.5 | ✓ |
| HSS1000 | 1000 | 900 x 2320 | | ✓ | | | ✓ |
| HSSE10001CF | 1000 | 900 x 2320 | ✓ | | 3.5 | | ✓ |
| HSSE10002CF | 1000 | 900 x 2320 | ✓ | | | 3.5 / 1.7 | ✓ |



Features

- Duplex 2205 Stainless Steel
- Polyurethane Foam Insulation
- Painted Metal Outer Case
(1000 Litre - Stainless Steel Outer Case)
- 6 x 50mm, 2 x 25mm Fittings
(1 x 25mm for PTR)
- 28mm Diameter Heat Exchange Coils
- 32mm Fittings on Heat Exchange Coils
- Large Surface areas for Heat Exchange Coils
- Thermowell Pockets
- 3.0kW Element standard on Coil Tanks
- Watermark Approved
- Australian Electrical Approvals
- Maximum Working Pressure – 700kPa





HYDRALUX

SMARTER HOT WATER

A quality product from Wilson Hot Water

130 - 140 Merrindale Drive

Croydon South VIC 3136

Free Call - 1800 302 050

sales@wilsonhotwater.com.au

wilsonhotwater.com.au

wilson
CUSTOMISED HOT WATER

